



P/N 5104

2005-09 Door Handle Installation Instructions

Thank you for your purchase of SilverHorse Racing products. Please read all directions before beginning Installation. A factory shop manual should be available for reference during installation. If, after reading these directions, you feel that you may not be able to complete the installation yourself; please seek out professional installation by certified technicians.

TOOLS REQUIRED:

T30 Torx bit / driver	6mm socket and ratchet / driver
Pick / hook tool	Safety glasses
Standard / Needle nose Pliers	Flat Screwdriver (small and large)

1. Roll down both windows.

3. Carefully pry the plastic cover away behind the stock handle and remove the T30 Torx head screw.



2. Remove negative terminal from battery.

4. The cover in the door pull / armrest area needs to be pried away, and the T30 Torx screw behind it removed.



5. Remove the window switch plate assy. by prying up the top cover and gently pulling out the entire switch assy. almost horizontally. Remove the plugs from the switches and remove the assy.



6. Remove the door lock bezel by slightly lift it up – a small screwdriver may be needed.



7. Using a 6mm socket, remove the (9) nine screws on the periphery of the door and the one hidden in the window switch area. See figure below for screw locations.



8. Pop off the plastic cover next to side mirror. Unplug wiring as needed.



9. Lift up on the interior panel, removing it from the door. Remove any remaining electrical connections.



10. Disconnect the door handle cable by rotating the plastic clip in the direction that allows you to pull the cable out.



11. Remove the cable and the spring inside the stock handle. Remember the orientation of the spring, which will be re-used with the new handle.

13. Snap the new handle into place by wiggling it into the door cup assembly. Re-install the spring that was removed from the original handle, making sure that it is all the way in the pocket with the bottom leg against the recess in the door panel to put tension on the handle to return it to the closed position when not in use. It is critical that the handle retract properly, otherwise the door could inadvertently open while the vehicle is in motion! Lubricate spring with a quality grease.



12. Remove the stock door handle from the cup by opening it to the full open position and prying up and down to pop it off the plastic studs in the handle cup.

14. Reinstall the door panel back onto the door, making sure to reconnect all connections as needed and that tabs that hold door at bottom are inserted properly. The reassembly is the reverse of steps 10-3. When both sides are complete, re-connect the battery and enjoy!

If you have any questions, feel free to contact us at the number listed below or via email.

Tech Questions: (321)-722-2813.
Email us -
CustServ@SilverHorseRacing.com

“If it’s not good enough for our cars, we won’t make them for yours.”

