



P/N S197-875 Plug-n-Play LED Light Kits

Thank you for your purchase of SilverHorse Racing products. Please read all directions before beginning the installation. A factory shop manual should be available for reference during installation. If, after reading these and any accompanying directions, you feel that you may not be able to complete the installation safely and properly, please seek out professional installation by certified technicians. Please read and understand our product purchase agreement (included on yellow sheet) prior to starting. Vehicle should be off with key removed from ignition and in park (if applicable) with parking brake set prior to beginning installation.

Expected installation time is 10 minutes for a first-time installer.

TOOLS / MATERIALS REQUIRED:

Small paper towel or rag, small flat screwdriver, small pick, Phillips screwdriver (optional)

1. Place vehicle in park and set emergency brake, then shut off if running.
2. With doors closed wait approximately 2-5 minutes for original incandescent bulbs to cool.
3. Remove small round dome light lens covers using a small flat screwdriver or pick. There is a small indentation on the lens that the tool can be pried in to snap the lens out safely.
4. Using a rag or paper towel to **avoid burning your fingers**, remove original bulbs.
5. Insert new LED bulbs. **LED bulbs are different than incandescent bulbs in that the direction of electrical flow is important. Before reinstalling the lens covers, check for proper operation by turning on the lights. If one or both bulbs do not illuminate, remove, rotate 180 degrees in the socket, and re-insert and check.**
6. Once bulbs are both working, reinstall lens covers and snap in place.

If you have received a trunk bulb:

7. Use a small flat screwdriver to pry the lens out from the back panel of the trunk, and replace the bulb. If needed, you may need to squeeze the clips closer together to get a firm grip on the ends of the festoon bulb. Insure that the replacement illuminates, if not, remove, rotate 180 degrees and reinstall. Before reinstalling lens into trunk, make sure LED elements are pointing towards trunk for best illumination.

If you have received license plate bulbs:

8. Normally the lenses are held in with a Phillips screw or unclip from the bumper using Phillips-style plastic rivets depending on model year. On the 05-09 model there is one 194 style bulb and the lens uses the plastic rivets to remove and install. On the 10-15+ model, there are two festoon bulbs, each held in by a single Phillips screw. Remove and replace / reinstall as required, and check for proper operation before final re-assembly. If the clips to the festoon ends are not tight, gently squeeze them closer together to insure a firm grip on the bulb.

If you have any questions, feel free to contact us at the number listed below or via email.

Tech Questions: (321)-722-2813.

Email us -

Tech@SilverHorseRacing.com

“If it’s not good enough for our cars, we won’t make it for yours.”

